

Mil-Spec Shrink Boot Adapter to Heat Shrink Boot Cross Reference

Shell Size	Finish		Lipped Heat Shrink Boots*	
	Nickel	Black	St. Boot	90° Boot
8	M85049/60-2G8N	M85049/60-2G8A	202K121-25-0	222K121-25-0
10	M85049/60-2G10N	M85049/60-2G10A	202K131-25-0	222K131-25-0
12	M85049/60-2G12N	M85049/60-2G12A	202K132-25-0	222K132-25-0
14	M85049/60-2G14N	M85049/60-2G14A	202K142-25-0	222K142-25-0
16	M85049/60-2G16N	M85049/60-2G16A	202K153-25-0	222K152-25-0
18	M85049/60-2G18N	M85049/60-2G18A	202K153-25-0	222K152-25-0
20	M85049/60-2G20N	M85049/60-2G20A	202K163-25-0	222K163-25-0
22	M85049/60-2G22N	M85049/60-2G22A	202K163-25-0	222K163-25-0
24	M85049/60-2G24N	M85049/60-2G24A	202L163-25-0	222K163-25-0

* Always use K series lipped boots on backshells, the lip on the boot is designed to engage the lip on the shrink boot adapter.

It is necessary to use adhesive when attaching the shrink boot to the shrink boot adapter. please see below for the required adhesive and dispensing equipment.

Adhesive For Shrink Boot Installation			
RT125	Adhesive Applicator	Adhesive Kit	Mixers